

### USES

Pavers, concrete and retaining walls. Can also be used on manufactured and natural stone, tile, terrazzo and stucco on both horizontal and vertical applications. Not recommended for wood, rubber, plastic, metal tiles or similar metallic surfaces.

### RELATED PRODUCTS

- SB-442 General Stain Remover
- SB-1300 Joint Stabilizing Sealer
- SB-600 Wet Look Sealer
- SB-4000 Water Repelling Invisible Sealer
- SB-5000 Stainblocking Invisible Sealer
- SB-7000 Gloss Finish Joint Stabilizing Sealer
- SB-10 Paver Bond®

Features	Benefits
What makes SB-488 Efflorescence & Rust Remover different?	
Powerful	• Dissolves chemical deposits
Water systems cleaner	• Removes hard water staining
Safe	• Does not contain muriatic, nitric or hydrochloric acid
Environmentally friendly	• Biodegradable and phosphate free
Clean Rinse Technology	• Does not leave cleaner residue on the surface
Compatible	• Works with all Surebond sealers
Versatile	• Works on both horizontal and vertical surfaces

### PRODUCT DESCRIPTION

SB-488 Efflorescence & Rust Remover is a safe, acid-based cleaner formulated specifically for use on pavers, concrete and retaining walls. The product quickly, safely and easily removes mineral deposits like efflorescence that form naturally within building materials and from external sources like rust and hard water. SB-488 Efflorescence & Rust Remover's unique Clean Rinse Technology lifting power allows deposits and residue to be quickly and easily rinsed away with a high or low pressure water sprayer. The product is suitable for both horizontal and vertical surfaces and is biodegradable and phosphate free. It does not contain muriatic, nitric or hydrochloric acid.

### PREPARATION

To determine the suitability of this product for a specific surface, test on a small, inconspicuous area first. Inspect area for visible staining to determine stain types and quantity. Sweep and remove all soil and other debris from the surface. Clean only the affected areas.

### APPLICATION INFORMATION

For best results use at full strength (never dilute). Dampen discolored area with water prior to application of cleaner. Use only cold water when cleaning and rinsing surfaces. Apply using a garden sprayer, low pressure siphon or bulk sprayer. Saturate affected area with cleaner and allow cleaner to sit on the surface to break down mineral deposits. Improve results by scrubbing surface with a natural fiber brush to agitate and break down deposits. Wear protective clothing and glasses. A high pressure wash can be used to further break down deposits. Rinse surface thoroughly after cleaning. It may be necessary to use secondary cleanings to remove heavier, deep set stains.



### MAINTENANCE

Pavement and wall maintenance should be carried out per instructions on appropriate sealer data sheet. Surebond cleaners are compatible with all Surebond sealers.

### COVERAGE\*

MATERIAL	SQ FEET	SQ METER
All surfaces	100 – 200	9.3 - 18.6

\*Per gallon. Coverage based on single treatment. Some applications may require additional treatments. Actual coverage may vary depending on the type, age, condition and porosity of the surface, application method and other local conditions.

### PACKAGING/SIZES

- 12 x 16 oz spray bottles per case
- 4 x 1 gallon containers per case
- 5 gallon pails
- 55 gallon drums
- Bulk packaging available

### STORAGE

Store container in a cool place and protect from freezing.

### SHELF LIFE

Two years when properly stored.

### PRECAUTIONARY INFORMATION

Eye irritant. Contains Organic Salt. Avoid getting product in eyes. Harmful if swallowed. Do not take internally. Avoid prolonged or repeated contact with skin.

FIRST AID: If in eyes, flush immediately with water for at least 15 minutes, then see a doctor. For skin, wash with soap and water. If irritation persists, see a doctor. If swallowed, do not induce vomiting. If conscious, give 3 - 4 glasses of water to dilute and see a physician immediately.

Keep out of reach of children (see Material Safety Data Sheet).

### LIMITATIONS

Do not expose containers to freezing temperatures and store inside during cold weather. Test cleaning is always recommended to ensure both the proper physical and aesthetic properties prior to starting a project. Do not use on wood, rubber, plastic, metal tiles or similar metallic surfaces.

### WARRANTY

Manufacturer warrants its products conform to the published specifications. No other warranties are expressed or implied, including those of merchantability or fitness or any purpose not expressly set forth herein. The user must determine suitability of the products for their particular use. Manufacturer and any seller's liability for incidental or consequential damage hereunder shall not exceed the purchase price of the product used.

### ASSISTANCE & ADDITIONAL INFORMATION

For sales, specification assistance, technical questions, detailing, etc., please contact:

#### SUREBOND

2801 International Lane

Madison, WI 53704 USA

Toll Free (US & Canada): 888-44SURE1 (888-447-8731)

Phone: (608) 237-7554

Fax: (608) 237-7558

Email: [info@surebond.com](mailto:info@surebond.com)

